

Questionnaire for manhole cover SD4/RC3/RC4

Project: _____

Customer: _____ Person in charge: _____ Phone: _____

Site: _____ Customer No.: _____ Fax: _____

☐ Offer Offer No.: _____ Price per unit: _____ €,

☐ Order Order No.: _____ Manufacturing costs per unit: _____ €, Item.: _____, Q: **P** _____

Short text: Manhole cover typ SD4-RC3/RC4, design based on DIN 1239:2018-4, burglar resistant to DIN 1627 resistance class RC3 or RC4, rainproof, seal low-wear in cover, completely made of stainless steel, cover plate 4 mm thick, including lock system with anti-drilling protection, as standard with hardened safety lock as; the profile cylinder in accordance with DIN 18252 to be provided by the customer.

1. Material:

☐ 1.4307 (AISI 304 L)

☐ 1.4404 (AISI 316 L)

2. Test certificate:

☐ RC3

☐ RC4

3. Test certificate:

☐ Design according to test certificate

☐ Design on the basis of the test certificate

RC3 and RC4 Maximum clear shaft opening, one-part design, with test certificate: Ø 1200 mm

4. Clear shaft opening:

Diameter Ø = _____ mm

Please note: Ø one part: min. 600 mm, max. 1300 mm
 Ø two part: min. 1200 mm, max. 1500 mm

5. Design:

☐ one-part

☐ two part

☐ Cross bar rigidly welded, not removeable

☐ Cross bar screwed, removeable (clear opening is reduced by 180 mm)

☐ Cross bar hinged

6. Frame:

☐ Frame for bolting with dowelling clips (standard)

☐ Frame for embedding into concrete (concealed frame)

7. Insulation and vapour hood:

- a) ☐ insulation of the cover ☐ special insulation height of the cover : _____ mm (max. 50 mm)
☐ insulation of the frame

- b) ☐ vapour hood DN 150, centrally welded

For multi-part covers:

- ☐ vapour hood on all cover parts ☐ vapour hood only left side ☐ vapour hood only right side

8. Optional equipment:

- ☐ Opening possibility from below (⇒ designed on the basis of the test certificate!)
- ☐ Magnetic contact (cover open/closed indicator)
- ☐ Detachable hinges, i. e. removable cover (⇒ designed on the basis of the test certificate!)
- ☐ Cover which can only be opened from below (with locking lever, without upper locking part) (⇒ designed on the basis of the test certificate!)
- ☐ Paint RAL colour: _____
- ☐ Biofilter in vapour hood (only DN 150) (odour elimination) *or*
(Info: retrofitting biofilter only possible with insulated covers)
- ☐ Energy self-sufficient wind-powered ventilator
- ☐ Cover on the top of the wall executed according to customer's structural drawing (Not with frame for setting in concrete)
 Width of the on-site wall crown: ____ mm / Frame bending downwards: ____ mm

9. Other accessories/Comments:

.....

.....

.....

.....

10. Sales person in charge:

..... Phone No.: +498462/201-____ Fax No.: +498462/201-399 E-mail:____@huber.de

11. Enclosures for the design engineers:

- ☐ Drawing ☐
- ☐ Photo ☐

Mounting material has to be recorded as a separate item:

Mounting material for SD4/RC3/RC4

- | | | |
|---|--|----------------|
| <input type="checkbox"/> X <input type="checkbox"/> | 10192423 – Mounting material for SD4/RC3/RC4 up to Ø 1000 | Price: € |
| <input type="checkbox"/> X <input type="checkbox"/> | 10192582 – Mounting material for SD4/RC3/RC4 ILLMOD bis Ø 1000 | Price: € |
| <input type="checkbox"/> X <input type="checkbox"/> | SPECIAL Mounting material for SD4/RC3/RC4 (Service article) | Price: € |
| <input type="checkbox"/> X <input type="checkbox"/> | 10238266 pollen filter, 1.4404, (exchangeable) in vapour hood DN 150 | Price: € |